



## PTB750S-05-5

TECHNICAL DATA		W:E183240 ©:228277
PITCH		7.62mm
ELECTRICAL RATING		300V, 15A
BREAKDOWN VOLTAGE		4,000V
MATERIALS		
INSULATION BODY		Nylon,UL94,V-0
TERMINAL		Brass,Tin Plated
OPERATING TEMPERATURE		-40°C ~ +105°C
PCB HOLE DIAMETER		ø1.6mm
*MATE WITH PLUG: PTB750B-05-5		

Positions	L	Positions	L
02	15.24	18	137.16
03	22.86	19	144.78
04	30.48	20	152.40
05	38.10	21	160.02
06	45.72	22	167.64
07	53.34	23	175.26
08	60.96	24	182.88
09	68.58		
10	76.20		
11	83.82		
12	91.44		
13	99.06		
14	106.68		
15	114.30		
16	121.92		
17	129.54		

## ORDERING INFORMATION

SERIES	STYLE	PITCH	POSITIONS	COLOR	OPTIONS*
PTB <input type="text"/> <input type="text"/> <input type="text"/> S	<input type="text"/> <input type="text"/>	<input type="text"/>	<input type="text"/> <input type="text"/>	<input type="text"/>	M <input type="text"/> <input type="text"/>
	00 to 99	1=5.00 2=5.08	02 to 24	0=Light Grey 1=Black 2=Blue 3=Green 4=Dark Grey	